



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company

Eastto Ban 330

INTRODUCTION: EASTTO BAN 330 is a high quality rust preventive of non-solvent type, blended from superior base stocks and specially selected additives to provide excellent protection of metal components against rusting for longer duration, both in indoor and outdoor applications. Because of its non-drying type, the removal of EASTTO BAN 330 is easier and does not require any special precautions during storage, handling and applications.

APPLICATION: EASTTO BAN 330 can be applied by immersion, brush, swab or spray for protecting iron components like nut bolt, automotive spare parts, steel tube pipes, nails, metal sheets etc. from the rusting when thick protective film of rust preventive oil is required by the engineering and other industries, particularly when the removal of protective oil film is not necessary for subsequent processing of the metallic components.

PERFORMANCE LEVEL : EASTTO BAN 330 is a proprietary product.

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO BAN 330
Kinematic Viscosity at 40°C., cSt	450
Film Thickness, Micron, Min.	30
Copper Strip Corrosion Test at 100°C for 3 Hrs.	1

PACKING: 210 Litres Drums



Eastto Ban 330



Eastern Petroleum Private Limited

Regd. Off.:
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in

