

**Eastto** Eastto Quench Oils **22, SPECIAL 22, 32, SPECIAL 32 AND 68**

**INTRODUCTION:** EASTTO QUENCH OILS are heat treatment oils blended from solvent refined base oils with specially selected additives that facilitate fast quenching through proper and controlled cooling, have outstanding chemical and oxidation stability. These oils also have excellent thermal properties, low volatility, high flash and fire points.

**APPLICATION:** EASTTO QUENCH OILS are used for different types of quenching operations on wide variety metallic parts. EASTTO QUENCH 22, EASTTO QUENCH 32 and EASTTO QUENCH 68 are straight mineral oil type quenching oils whereas EASTTO QUENCH SPECIAL 22 and EASTTO QUENCH SPECIAL32 are compounded type quenching oils.

**PERFORMANCE LEVEL:** EASTTO QUENCH OILS meet IS: 2664 – 1980 (RA 2004)

**TYPICAL PROPERTIES**

PROPERTIES	EASTTO QUENCH 22	EASTTO QUENCH SPECIAL 22	EASTTO QUENCH 32	EASTTO QUENCH SPECIAL32	EASTTO QUENCH 68
Kinematic Viscosity at 100°C., cSt,	22 to 24	22 to 24	32 to 34	32 to 34	66 to 70
Viscosity Index, Min.	90	90	90	90	90
Flash Point, COC, °C.	190	190	190	190	190
Pour Point, °C. Max.	-6	-3	-6	-3	-6

**PACKING:** 210 Litres Drums



## **Eastto** Eastto Quenching Oils



**Eastern Petroleum Private Limited**

Regd. Off.:  
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,  
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.  
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990  
Email: office@easternpetroleum.in, office@eastto.in,  
Web: www.easternpetroleum.in, www.eastto.in

