

Eastto Rio 30, 40

GRADE: SAE 30, 40

INTRODUCTION:

Eastto Rio 30 and EASTO Rio 40 are suitable for preservation-cum running-in oil and also as engine oil for driving away the chassis. They have excellent wear and rust control with superior performance.

APPLICATION:

EASTTO Rio 30 and EASTO Rio 40 are used mainly as "Preservation and Running-in-oil" for the Automobile Industries. They can also be used for engine scheduled for export where time lag between production of engines and use by the customers is quite fill oil prior to sale and protect the engine parts from sea water during shipment and storage.

PERFORMANCE LEVEL: Meets the performance level of API CD, IS: 13656-2014, EDL-2

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO Rio 30	EASTTO Rio 40
Kinematic Viscosity at 100°C, cSt,	11.5	14.5
Flash Point, COC, °C	230	230
TBN, mg KOH / gm	10.5	10.5
Pour Point, °C, Max.	(-) 6	(-) 6

PACKING: 210 Litres Drum



Eastern Petroleum Private Limited

Regd. Off.:

Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto
Rio 30, 40