

Eastto Ultra TC 10W, 30, 40, 50

GRADE: SAE 10W, 30, 40, 50

INTRODUCTION:

Eastto Ultra TC 10W, 30, 40, 50 are heavy duty diesel engine oils blended from highly refined base stocks and selected additives, and they have high level of detergency, excellent thermal and oxidation stability with superior performance under severe conditions.

APPLICATION:


EASTTO Ultra TC 10W, 30, 40, 50 are recommended for turbocharged diesel engines of heavy duty commercial vehicles, earth moving equipments, multi utility vehicles etc

PERFORMANCE LEVEL: Meets the performance level of API CD, IS: 13656-2014, EDL-2

TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO ULTRA TC 10W	EASTTO ULTRA TC 30	EASTTO ULTRA TC 40	EASTTO ULTRA TC 50
Kinematic Viscosity at 100°C, cSt	5 Min.	10.0 - 12.0	13.0 - 15.0	18.0 - 20.0
Viscosity Index, Min.	100	90	90	90
Flash Point, COC, °C, Min.	220	220	220	220
TBN, mg KOH / gm	9.0 - 11.0	9.0 - 11.0	9.0 - 11.0	9.0 - 11.0

PACKING: 210. 20 Litres Drum



Eastern Petroleum Private Limited


Regd. Off.:

Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto
Ultra TC 10W, 30, 40, 50