

Eastto API CF-4 15W-40, 20W - 40

INTRODUCTION:

Eastto GEM CF-4 15W-40, 20W-40 are premium quality API CF- 4 15W-40 and 20W-40 diesel engine oils. These are blended from highly refined base stocks and superior quality additives for high viscosity index and excellent detergent-dispersant inhibition to keep engine clean, prevent oil degradation / thickening and corrosive wear. Other features include long draining periods, extended TBN retention and reduced oil consumption with better fuel economy.

APPLICATION:

They are recommended for diesel passenger cars and commercial heavy duty diesel engines on-highway and off-highway equipment, like mining, earthmoving, construction industry and DG sets, and also for gasoline engines.

PERFORMANCE LEVEL: Meets the performance level of API CF- 4 / SG, IS: 13656-2014, EDL-5 / EPL-3, MB 228.1 and MIL-L-2104E

TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO GEM CF- 4 15W-40	EASTTO GEM CF- 4 20W-40
Kinematic Viscosity at 100°C., cSt,	14.0	14.50
Flash Point, COC, °C. Min.	210	210
TBN, mg KOH / gm	10.5	10.5
Pour Point, °C. Max.	(-)21	(-)21

PACKING: 210 Litres Drum



Eastern Petroleum Private Limited

Regd. Off.:

Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto Gem Cf- 4 15w-40, 20w- 40