

Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

PRODUCT DATA SHEET

PRODUCT:

INTRODUCTION:

EASTTO GEN SET OIL SAE 20W-40

EASTTO GEN SET OIL SAE 20W-40 is multi grade diesel engine oil blended from highly refined base stocks with high viscosity index and additives that impart detergent, dispersant, anti-oxidant and anti-w ear properties. Besides low ering the maintenance cost, **EASTTO GEN SET OIL SAE 20W-40** enhances the engine life with less w ear and tear and controlling sludge and varnish.

APPLICATION:

EASTTO GEN SET OIL SAE 20W-40 is recommended for use as crankcase oils for slow, medium and high speed stationary diesel engines.





PERFORMANCE LEVEL:	
--------------------	--

EASTTO GEN SET OIL SAE 20W-40 meets the performance level of API CF, IS: 13656-2002, EDL-2

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO GEN SET OIL SAE 20W-40
Kinematic Viscosity at 100°C, cst	15
Flash Point, COC,°C, Min.	220
TBN, mg KOH / gm	10
Pour Point, °C	-21

PACKING: 210 Litres Drum

Date of issue: 09.09.2014

Date of revision: 26.08.2016

1st Revision: 30.05.2019 (CK)

PDS No. 01.15.02

These Characteristics are typical of current production w hile future production w ill confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

