

PRODUCT DATA SHEET

PRODUCT:	EASTTO AUTOMATIC TRANSMISSION FLUID A
GRADE:	TYPE A SUFFIX A OF DEXTRON 1 AND 1B OF GENERAL MOTORS, USA

INTRODUCTION: **EASTTO AUTOMATIC TRANSMISSION FLUID A** is a premium quality red coloured transmission fluid with low co-efficient of friction to meet Type A Suffix A specification of General Motor. **EASTTO AUTOMATIC TRANSMISSION FLUID A** is blended with highly refined base stock fortified with carefully selected additives to impart good resistance to thermal oxidation, very low temperature flow characteristics, and excellent seal compatibility with anti-wear and anti-corrosion properties. This high viscosity index oil ensures smooth power shift operation with minimum power loss.

APPLICATION: **EASTTO AUTOMATIC TRANSMISSION FLUID A** recommended for use in both passenger cars and light trucks requiring Type A Suffix A fluid for Automatic Transmission and Power Steering Systems and Synchromesh Gear System.



Automatic Transmission, Power Steering Systems and Synchromesh Gear System.

PERFORMANCE LEVEL: Meets the performance level of A SUFFIX A OF DEXTRON 1 AND 1B OF GENERAL MOTORS, USA

TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO AUTOMATIC TRANSMISSION FLUID A
Kinematic Viscosity at 100°C, cst	7.2
Viscosity Index, Min.	150
Flash Point, COC, °C.	180
Pour Point, °C.	(-) 39

PACKING: 210 Litres Drums.

Date of issue: 01.07.2014

Date of revision: 26.08.2016

PDS No. 01.35.01

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

