

Product Data Sheet

PRODUCT: EASTTO CALIBRATION FLUIDS 2, 5

GRADE: VG 2, 5

INTRODUCTION:

EASTTO CALIBRATING FLUIDS 2, 5 are simulated fuels with properties similar to diesel fuel. These specially developed fluids are not only safer to use, but are formulated to meet tighter, more demanding specifications required in the manufacturing processes used by the fuel system component manufacturers when building fuel pumps, fuel injectors and fuel, air and oil filters. These fluids contain a range of special additives to enhance corrosion resistance, oxidation stability and anti-wear. **EASTTO CALIBRATING FLUIDS 2, 5** are more suitable than commercially refined fuels for use in manufacturing processes due to the precisely controlled viscosity, density, higher & safer flash points and lower aromatic hydrocarbon content.

APPLICATION:

EASTTO CALIBRATING FLUIDS 2, 5 are recommended for the calibration of fuel pumps, fuel injectors and fuel, air and oil filters.



Diesel fuel.



Fuel pumps.



Fuel injectors.

PERFORMANCE LEVEL: Meets the performance level of ISO: 4113

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO CALIBRATION FLUIDS 2	EASTTO CALIBRATION FLUIDS 5
Kinematic Viscosity at 40°C, cSt	1.98 -2.42	4.14 – 5.06
Flash Point, PMCC, °C, Min.	75	130
Pour Point, °C. Max.	(-) 6	(-) 6

PACKING: 210 Litres Drums.

Date of issue: 04.09.2014

PDS No. 01.50.01 – 01.50.02

DISCLAIMER: The information given here is considered to be correct and is offered for your consideration, investigation and verification. No warranties are expressed or implied, since the end use of products are beyond our control.

