

PRODUCT DATA SHEET

PRODUCT: EASTTO GEM 15W-40, 20W- 40 CF- 4

INTRODUCTION: EASTTO GEM 15W-40, 20W-40 CF- 4 are premium quality diesel engine oils. These are blended from highly refined base stocks and superior quality additives for high viscosity index and excellent detergent-dispersant inhibition to keep engine clean, prevent oil degradation, thickening and corrosive wear. These oils provide long draining periods, extended TBN retention and reduced oil consumption with better fuel economy.

APPLICATION: They are recommended for diesel passenger cars and commercial heavy duty diesel engines on-highway and off-highway equipment, like mining, earthmoving, construction industry and DG sets, and also for gasoline engines.



Heavy duty diesel engines on-highway and off-highway like mining, earthmoving construction industry and DG sets.

PERFORMANCE LEVEL: Meets the performance level of API CF- 4 / SG, IS: 13656-2014, EDL-5 / EPL-3, MB 228.1 and MIL-L-2104E

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO GEM 15W-40 CF- 4	EASTTO GEM 20W-40 CF- 4
Kinematic Viscosity at 100°C,	14.0	14.50
Flash Point, COC, °C, Min.	210	210
TBN, mg KOH / gm	10.5	10.5
Pour Point, °C.	- 21	- 21

PACKING: 210 Litres Drums

Date of issue: 06.09.2014

Date of revision: 26.08.2016

PDS No. 01.07.01 – 01.07.02

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

