

PRODUCT DATA SHEET

PRODUCT:
EASTTO MULTIGRADE OIL 10W-30, 20W-40, 20W-50
INTRODUCTION:

EASTTO MULTIGRADE 10W-30, 20W-40, 20W-50 are blended from highly refined base stocks and specially selected additives to meet special characteristics and performance levels, like excellent thermal and oxidation stability, protection against rust, corrosion and wear. They have very high viscosity index to provide ease in starting and ensure adequate oil film thickness at extreme temperature to eliminate seasonal oil changes. It reduces the oil consumption and keeps the engine clean.

APPLICATION:

EASTTO MULTIGRADE 10W-30, 20W-40, 20W-50 oils are recommended for use in gasoline and diesel engines operating over wide range of temperatures throughout the year.



Gasoline and diesel engines operating over wide range.

PERFORMANCE LEVEL: Meet the performance level of **API CC/SC**, MIL-L-2104 B and IS: 13656-2014, E-PL1/E-DL1.

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO MULTIGRADE 10W-30	EASTTO MULTIGRADE 20W-40	EASTTO MULTIGRADE 20W-50
Kinematic Viscosity at 100°C, cst	12	14	18
Flash Point, °C Min.	190	200	200
TBN, mg KOH / gm	6.0	6.0	6.0
Pour Point, °C	- 24	- 21	- 21

PACKING: 210 Litres Drum

Date of issue: 06.09.2014

Date of revision: 26.08.2016

PDS No. 01.04.01 – 01.04.03

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

