

Eastto *Shuttering Oil*



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company

Eastto Shuttering Oil (Conmold Oil)

Brand: Eastto Shuttering Oil

Introduction:

Eastto Shuttering Oil is an oil based concrete mold releasing oil, blended from specially selected base oils and excellent additive package for molds in concrete construction works. It offers outstanding de-moulding performances with good surface finish to the molded products. It is non – toxic and does not create misting during spraying or by other applications.

Application:

Eastto Shuttering oil is recommended for all types of normal and complex concrete molds including railway sleepers, all types of slab casting, beam, columns, staircase foundations, wall, pipes, poles etc.

Typical Properties:

CHARACTERISTICS	EASTTO CONMOLD OIL	Unit
Description	Premium quality general purpose concrete release oil incorporating special oiliness additive. Can be used by brush, swab, spray or dipping.	
Colour	Pale Yellow	
Appearance	Bright & Clear	
Viscosity at 40 degree	7.25	cSt
Density at 29.5	.835	Gram/cc

Coverage: A Coverage of 30 – 60 sq mtr per Ltr by spray is possible depending upon the surface texture. Steel or plastic form work will give best result with maximum coverage. Timber form work, coverage will be lesser.

Shelf Life: 1 year when stored in original & unopened container under covered space.

Precaution / Limitations: To be used in well ventilated condition, since oil is flammable. Avoid prolong skin contact.

Packing: 210 Litres Drum

Date of issue: 18.05.2015.

Eastern Petroleum Private Limited

Regd. Off: Unit 1, Corporate Park, Chembur, Mumbai - 400 071

T | + 91 - 22 - 4232 4121 / 2529 9990 F | + 91 - 22 - 2524 1895.

E | office@easternpetroleum.in

W | www.eastto.in

