

Eastto Mist Oils

GRADE: VG 32, 46, 68 and 100

INTRODUCTION:

Eastto Mist Oils, 32, 46, 68 and 100 have been formulated from high quality solvent refined base stocks and a specially selected additive system particularly for optimum reclassifying or agglomerating properties. They have high resistance to oxidation, good extreme pressure, anti-rust and anti-wear properties with enhanced surface wetting capabilities.

APPLICATION: EASTTO MIST OILS are suggested for the oil-fog or mist-lubrication of machine components such as slide ways, slow-speed and industrial gearing such as cooling tower, gearboxes, high-speed bearings, chain, machine tools.

PERFORMANCE LEVEL: Proprietary

TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO MIST OILS			
	32	46	68	100
Kinematic Viscosity at 40°C, cSt	30 to 34	44 to 48	64 to 72	95 to 105
Viscosity Index	95	95	95	95
Flash Point, COC, °C, Min.	200	200	210	220
Pour Point, °C. Max.	-12	-12	-12	-12

PACKING: 210 Litres Drum



Eastern Petroleum Private Limited

Regd. Off.:
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto Mist Oils