

## Eastto Turbine Oils

GRADE: 32, 46, 57, 68 & 76.

### INTRODUCTION:

These oils are blended from highly refined turbine base stocks containing antioxidant, rust inhibitor and antifoam additives. They have excellent thermal stability and demulsibility.

**APPLICATION:** Recommended for lubrication of steam, gas and hydraulic turbines

**PERFORMANCE LEVEL :** Meet IS – 489 - 1983 Specifications, BIS – 1012 - 1987 (Reaffirmed 1993), Meet General Electric GEK 27070 Specification, KWU (Siemens) W. Germany.

### TYPICAL PROPERTIES:

EASTTO TURBINE OILS					
CHARACTERISTICS	32	46	57	68	76
Kinematic Viscosity @ 40°C, cSt.	30 to 34	44 to 48	54 to 60	66 to 70	74 to 78
Viscosity Index, Min.	100	100	98	98	98
Flash Point, °C, COC, Min.	200	200	210	210	220
Pour Point, °C, Max.	-9	-9	-9	-9	-9

**PACKING :** 210 Litres Drum



### Eastern Petroleum Private Limited

Regd. Off.:  
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,  
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.  
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990  
Email: office@easternpetroleum.in, office@eastto.in,  
Web: www.easternpetroleum.in, www.eastto.in



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



## Eastto Turbine Oils