

PRODUCT DATA SHEET

PRODUCT: EASTTO METALHONE TX

GRADE: VG 5

INTRODUCTION: EASTTO METALHONE TX is a very light coloured and low viscosity oils with excellent lubricity characteristics for honing operations of all ferrous and non-ferrous metals with good surface finish. This oil has excellent chip flushing, good heat carrying capacity and better visibility of work piece and tool, and provides long life to the honing stone.

APPLICATION: EASTTO METALHONE TX is suitable for machining of operations, like Turning, Drilling, Tapping, Honing, Broaching and Boring of all ferrous and non-ferrous metals and their alloys where non-staining type light coloured and low viscosity oil is required.



Honing Application

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO METALHONE TX
Kinematic Viscosity at 40°C, cst	5
Flash Point (COC)°C	130
Copper Strip Corrosion for 3 Hrs. at 100°C.	1
Pour Point, °C	-9

PACKING: 210 Litres Drums

Date of issue : 10.11.2014

Date of revision: 04.08.2016

PDS No. 05.50.01

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

