

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

MATERIAL SAFETY DATA SHEET

1. **Product name and Company identification**

Product Name	:	EASTTO INK OIL
Product Use	:	Industrial lubricants, Paints and Inks
Supplier	:	Eastern Petroleum Pvt. Ltd 235-239, Jawahar industrial Estate, Kamothe, Panvel, Dist- Raigad, Maharashtra: 410209
Telephone No.	:	91-22-2743 1694, 91-22-2743 3819.
Email	:	sales@easternpetroleum.in

2. **Composition / Information of Ingredients**

	Ingredient name	CAS Number	% by wt
	Hydro treated Base oil	64742-46-7	100
3.	Hazards identification	Non hazardous substance	
	Physical state	Liquid	
	Human Health Effects		
	Eyes	May mild irritation only if directly contact with	eyes.
	Skin	May cause skin irritation if prolonged use	
	Inhalation	May cause respiratory infection	
	Chemical Hazards	Combustible liquids	
4.	First Aid Measures		
	Inhalation	If inhaled, remove to fresh air. Get medical att	tention if symptoms occur.
	Skin contact	Immediately wash affected area with soap and water. Remove contamir clothing and shoes. Get medical attentions if a symptom occurs. In case of contact immediately wash eyes with plenty of water.	
	Eye contacts		
	Ingestion	Do not induce vomiting unless directed to c give anything by mouth to an unconscious quantities of this material have been swallo Get medical attention if symptoms occur.	s person. If potentially dangerous
5.	Fire-fighting Measures		
	Flammability of product	Combustible liquid	
	Extinguishing Media Suitable Not suitable	Use dry chemical, carbon dioxide (CO_2), or fo Do not use water.	am

6. **Accidental Release Measures**

Personal precautions	Wear suitable protection clothing and equipment. Remove contaminated clothes as soon as possible.
Environmental precautions	Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers. Inform local authorities if this cannot be prevented. Pick up free liquid for recycling or disposal. The residual oil can be transferred to another container.



Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

Clean up method- small spillage	Absorb liquid with sand or earth, sweep up and remove to a suitable, clearly
	marked container for disposal in accordance with local regulation.
Clean up methods – large spillage	Prevent from spreading by making a barrier with sand, earth or other
	containment material. Reclaim liquid directly or in an absorbent. Dispose of as for
	small spills.

7. Handling and Storage

Handling	Handle in accordance with good industrial hygiene and safety practices. If handled at elevated temperatures or with high speed mechanical equipment, vapors or mists might be released and require a well ventilated workplace.
Storage	Store at ambient temperature or with lowest necessary heating as required for ease of handling.

8. **Exposure Controls / Personal Protection**

Control parameters	Use under well ventilated area	
Personal protection equipment	protection equipment	
Respiratory protection Hand protection Eye protection Skin and body protection Hygienic measures	Avoid inhalation use suitable mask with filter if necessary. Wear oil-resistant protective gloves if there is a risk of skin contact. For eyes protection wear safety goggles. Use protective cloths and gloves. Act in accordance with good industrial Hygiene and safety practice.	

9. **Typical Physical and Chemical Properties**

CHARCTERISTICS	EASTTO INK OIL
Physical state	Liquid
Colour	Colourless
Odour	Odourless
Solubility in water	Insoluble
Flash point ⁰ C	107
Sp. Gravity @ 30 °C, gm/ml	0.78
Kinematic Viscosity @ 40 °C, cst	2.1

10. **Stability and Reactivity**

	Reactivity and stability Conditions to avoid Hazardous decomposition products Hazardous polymerization	Stable at normal conditions and decompose at higher temperature. Fire, flame, heating and highly oxidizing agents Hazardous decomposition products are not expected to form during normal storage. Under normal conditions of storage and use, polymerization will not occur.
11.	Toxicological Information	
	Potential chronic health effects Carcinogenicity	No known significant effects or critical hazards.
12.	Ecological Information	
	Environment effect:	Will not have chronic effect on aquatic environment
13.	Disposal considerations	
	Waste disposal procedure:	Place contaminated materials in a disposable container and dispose of in accordance with Local, State environmental regulations and contact local environment and health authorities to get the permission for waste disposal.
14.	Transport Information	Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)
15.	Regulatory Information EASTTO INK OIL	Not classified as hazardous. Date of issue: 20.12.2014



Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

16. Other Information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material in combination with any other materials or in any process, unless specified in the text.