

PRODUCT DATA SHEET

PRODUCT: EASTTO CONMOL OILS 5, 22

INTRODUCTION: EASTTO CONMOL OILS 5, 22 are high quality mineral oil based mould releasing oils with multi-purpose mould releasing agents for metallic and wooden moulds in concrete construction works. These oils form an excellent oily film on the mould surface that prevents rusting of mould and the release agents prevent concrete clinging to the moulds with a high quality surface finish. These oils does not causes stain or discolouration, interfere with drying process and is also not absorbed by the concrete

APPLICATION: EASTTO CONMOL OILS 5, 22 are recommended to use neat and it can be applied by spraying guns, rollers or by brushes prior to pouring aerated concrete and are recommended for use as a concrete mould release agent with the protection of moulds from rust.



Oils are applied by spraying guns, rollers, moulds, etc.

PERFORMANCE LEVEL: Proprietary product

TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO CONMOL	
	5	22
GRADE	5	22
Kinetic Viscosity at 40°C., cst	5	22
Colour, ASTM, Max.	3.0	3.0
Flash Point, °C, Min.	120	160
Pour Point, °C.	-3	-3

PACKING: 210 Litres Drums

Date of issue: 10.11.2014

Date of revision: 24.08.2016

PDS No. 07.04.01 – 07.04.02

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

