

## PRODUCT DATA SHEET

**PRODUCT:** EASTTO LOOM OILS N 22, 32, 46, 68, 100, 150, 220, 320, 460

**INTRODUCTION:** EASTTO LOOM OILS N are highly refined base oils have good inherent oxidation and thermal stability, non-corrosive properties.

**APPLICATION:** EASTTO LOOM OILS N are generally suggested for non-critical all loss lubrication systems of textile and other looms which do not require additive containing oils. These oils can also be used for other oiling applications of some equipment.



**PERFORMANCE LEVEL:** IS: 493 (Part 1):1981 [Reaffirmed 2004]

### TYPICAL PROPERTIES:

EASTTO LOOM OILS N									
Characteristics	22	32	46	68	100	150	220	320	460
Kinematic viscosity at 40°C	22	32	46	68	100	150	220	320	460
Viscosity Index	90	90	90	90	90	90	90	90	90
Flash Point, COC, °C.	180	190	190	210	220	230	230	240	250
Pour Point, °C.	-6	-6	-6	-6	-6	-6	-6	-3	-3

**PACKING:** 210 Litres Drum

**Date of issue:** 10.11.2014

**Date of revision:** 24.08.2016

**PDS No.** 10.30.01 – 10.30.09

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

